

## Tablet Case by LoveQuilting.com



Finished Size: 8" x 10" closed; 16-1/2" x 10" open

WOF = Width of Fabric  
RST = Right Sides Together  
WST = Wrong Sides Together

All seams are 1/4", unless noted otherwise

Fabric Cutting Requirements:

Front:

2 pieces fabric 6-1/2" x 10-1/2"  
1 piece fabric 5-1/2" x 10-1/2"  
1 Scrap for closure – cut 2 from closure template

Lining:

2 pieces 8-3/4" x 10-1/2"

Pocket:

1 piece 8-3/4" x 8"

Fusible stabilizer:

1 pieces 17-1/2" x 10-1/2"  
1 piece 8-3/4" x 4"  
1 Scrap for closure – cut 1 from template

Fusible Fleece:

1 piece 17-1/2" x 10-1/2"

1 Button 1 to 1-1/2"

1/2" Elastic – 4 pieces x 4"



### **POCKET**

Fold pocket in half so it measures 4" x 8-3/4", press. Open and place fusible stabilizer at press line and press into place. Top stitch at folded edge and set aside.



### **CLOSURE TAB**

Fuse stabilizer to wrong side of one closure pieces. With RST, sew 1/4" on all sides of closure EXCEPT side marked "Raw Edge" on template. Clip corners, turn, press and top stitch 1/4" around all sides EXCEPT "Raw Edge" side. Make a buttonhole to accommodate your button having the start of the buttonhole 1" from the point. Set aside.



### **FRONT**

Sew front pieces together as shown. Press seams open. Fuse fleece to back side of front, then stitch as desired.



Find the center of the right side of front piece that will be the back of the case when in use, and mark it. Find the center of the raw side of the closure tab and mark it. Matching up center points, place raw edge of closure tab on RIGHT side of the front piece where marked, lining up raw edges, with tab facing in and stitch in place with 1/4" seam.

### **LINING**

Baste sides and bottom of pocket to the right side of one lining piece, matching up bottom edges.

On right side of other lining piece, at the corner, measure 1/2" from the side and make a mark, measure 2-1/2" from the top and make a mark. Place a piece of elastic diagonally at these marks and stitch in place. Repeat for other 3 corners. Be careful not to stretch the elastic.



Trim elastic to edges of lining. Sew right and left lining pieces together and fuse stabilizer to wrong side.



### **FINISHING**

Place lining RST to front piece lining up the side with elastic strips RST with front piece containing closure tab, and stitch all around with 1/4" seam. Clip corners, press and top stitch 1/8" all around. Enjoy your tablet case!



